

Armour Tyre

Off-the-road tyres

SIZE	PATTERN SERIA NUMBER	PR	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	RELEVANT PRESSURE	MAXLOADING
23.5-25 TL	L3	20PR	19.00/2.5	1615	595	390	10630
23.5-25TL	L5	20PR	19.00/2.5	1673	595	390	10630
23.5-25	L3	16PR	19.00/2.5	1615	595	320	9470
23.5-25TL	L3	16PR	19.00/2.5	1615	595	320	9470
23.5-25TL	L2	16PR	19.00/2.5	1615	595	320	9470
23.1-26	C2	12PR	DW20	1500	595	170	3655
21L-24	TI200	14PR	DW18L	1378	533	250	4200
20.5-25TL	L5	20PR	17.00/2.0	1548	520	460	9070
20.5-25TL	L3	20PR	17.00/2.0	1490	520	460	9070
20.5-25	L3	16PR	17.00/2.0	1490	520	350	7730
20.5-25TL	L2	16PR	17.00/2.0	1490	520	350	7730
20.5-25TL	L3	16PR	17.00/2.0	1490	520	350	7730
19.5L-24	TI200	12PR	17.0	1314	495	230	3450
18.00-24	R6	12PR	13.0	1590	500	350	5490
17.5-25TL	L5	16PR	14.00/1.5	1398	445	460	7020
17.5-25	L3	16PR	14.00/1.5	1350	445	460	7020
17.5-25	L3	14PR	14.00/1.5	1350	445	420	6650
17.5-25	L3	12PR	14.00/1.5	1350	445	350	5980
17.5-25TL	L3	12PR	14.00/1.5	1350	445	350	5980
17.5-25	L2	12PR	14.00/1.5	1350	445	350	5980
16.9-28TL	TI200	14PR	DW15	1410	429	300	3765
16.9-24TL	TI200	14PR	DW15	1310	429	300	3530
405/70-20TL	R1	14PR	13.0	1075	410	450	3075
16/70-20	R5	14PR	13.0	1075	410	450	3075
15.5-25TL	L3	12PR	12.00/1.3	1275	395	390	5300
15.5-25TL	L2	12PR	12.00/1.3	1275	395	390	5300
14.00-24	T5	24PR	10.0	1370	375	630	4580
14.00-24TL	L2	16PR	9.00DC	1348	362	350	3300
14.00-24TL	L2	12PR	9.00DC	1348	362	250	2725
13.00-24TL	L2	12PR	9.00DC	1278	333	300	2725
11.00-20	C1	16PR	8.0	1070	291	740	5430
10.00-20	TI300	16PR	7.5	1055	278	740	3470
9.00-20	C1	14PR	7.0	1002	256	740	4360
9.00-20	TI300	14PR	7.0	1018	259	700	2960
23*8.5-12TL	SK800	6PR	7.0	574	213	340	820
27*8.5-15TL	SK800	6PR	7JA	678	213	310	710
27*10.5-15TL	SK800	8PR	8LB	691	259	410	860
27*10.5-15TL	SK800	6PR	8LB	691	259	310	750
12.5/80-18TL	IMP600	12PR	11×18	1001	350	370	2625
12.5/80-15.3TL	M13	14PR	9.0	875	307	510	2810
12-16.5TL	RG400	12PR	9.75	831	307	520	1836
12-16.5TL	RG400	10PR	9.75	831	307	410	1612
12-16.5TL	SK300	10PR	9.75	831	307	410	1612

12-16.5TL	SK800	10PR	9.75	831	307	410	1612
12-16.5TL	RG500	10PR	9.75	831	307	410	1612
12-16.5TL	SK900	10PR	9.75	831	307	410	1612
12-16.5TL	RG500	8PR	9.75	831	307	310	1362
12-16.5TL	SK900	8PR	9.75	831	307	310	1362
12-16.5TL	SK800	8PR	9.75	831	307	310	1362
12-16.5TL	SK300	8PR	9.75	831	307	310	1362
11.5/80-15.3TL	M13	14PR	9.0	865	290	480	2350
11.5/80-15.3TL	M13	12PR	9.0	865	290	410	2145
11.5/80-15.3TL	R1	10PR	9.0	865	290	340	1930
10.5/80-18TL	IMP600	10PR	9×18	912	274	350	1630
10-16.5TL	RG400	12PR	8.25	773	264	620	1600
10-16.5TL	RG400	10PR	8.25	773	264	520	1423
10-16.5TL	SK800	10PR	8.25	773	264	520	1423
10-16.5TL	SK900	10PR	8.25	773	264	520	1423
10-16.5TL	TI200	10PR	8.25	773	264	520	1423
10-16.5TL	TI200	8PR	8.25	773	264	410	1250
10-16.5TL	SK900	8PR	8.25	773	264	410	1250
10-16.5TL	SK800	8PR	8.25	773	264	410	1250
10-16.5TL	RG400	8PR	8.25	773	264	410	1250
10-16.5TL	SK300	8PR	8.25	773	264	410	1250
10-16.5TL	SK300	6PR	8.25	773	264	310	1060
10/75-15.3TL	M13	14PR	9.0	780	264	510	1850
10/75-15.3TL	M13	12PR	9.0	780	264	460	1700
10/75-15.3TL	M13	10PR	9.0	780	264	390	1525
10/75-15.3TL	R1	10PR	9.0	780	264	390	1525

Agricultural tyres

SIZE	PATTERN SERIA NUMBER	PR	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	RELEVANT PRESSURE	MAXLOADING
21L-24TL	R4	14PR	18.0	1378	533	250	4200
21L-24TL	R4	12PR	18.0	1378	533	220	3875
19.5L-24TL	R4	12PR	17.0	1314	495	230	3450
19.5L-24	R2	10PR	W16L	1382	495	170	2120
18.4-42	R1	10PR	W16A	1857	467	180	3000
18.4-34	R1	8PR	W16L	1655	467	140	2565
18.4-30	R1	8PR	W16L	1550	467	140	2415
18.4-26	R1	12PR	DW16	1450	467	230	2265
18.4-26TL	R1	12PR	DW16	1450	467	230	2265
17.5L-24TL	R4	10PR	15.0	1241	445	220	2800
16.9-34	R1	8PR	W15L	1585	430	170	2380
16.9-30	R1	8PR	W15L	1485	430	170	2245
16.9-28	R1	8PR	W15L	1435	430	170	2175
16.9-24	R4	12PR	15.0	1310	429	260	3250
15.5/80-24TL	R1	12PR	W13	1262	394	300	2900
15-24	R1	10PR	DW14	1330	410	280	2800

14.9-30	R1	10PR	W13	1415	378	230	2190
14.9-30	PR1	8PR	W13	1560	378	180	1940
14.9-30	R1	8PR	W13	1415	378	180	1940
14.9-30	R7	8PR	W13	1415	378	180	1940
14.9-28	R1	8PR	W13	1365	378	180	1650
14.9-28	R7	8PR	W13	1365	378	180	1650
14.9-24	R1	4PR	13.0	1265	378	100	1120
14-17.5TL	R4	14PR	10.5	921	349	690	2800
13.6-38	R1	10PR	W12	1565	345	250	1950
13.6-38	PR1	10PR	W12	1710	345	250	2780
13.6-24	R1	8PR	W12	1210	345	200	1360
12.4-28	R1	8PR	W11	1260	315	230	1330
12.4-28	R1	6PR	W11	1260	315	170	1120
12.4/11-28	PR1	8PR	W11	1315	315	220	1900
12.4/11-28	PR1	6PR	W11	1315	315	200	1785
12.4-26	R1	6PR	W11	1210	315	170	1235
12-38	R1	10PR	DW11	1575	330	220	1800
12-38	R1	8PR	DW11	1575	330	140	1570
11.2-28	R1	6PR	W10	1205	285	180	1115
11.2-24	PR1	6PR	W10	1205	285	210	1465
11.2-24	R1	6PR	W10	1105	285	180	1045
11.2-20	M9	10PR	W10	1005	285	300	1250
11.2-20	M9	4PR	W10	1005	285	130	758
11-32	R1	6PR	W10	1360	305	140	1000
11-32	PR1	6PR	W10	1490	305	160	1080
10.00-15	F2	8PR	9.00.	770	258	240	2450
10.00-15	R1	8PR	9.00.	770	258	240	2450
9.5-24	R1	8PR	W8	1050	240	280	1110
9.5-24	PR1	8PR	W8	1150	240	310	1420
9.5-24	R1	6PR	W8	1050	240	210	940

Truck tyres

SIZE	PATTERN SERIA NUMBER	PR	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	RELEVANT PRESSURE	MAXLOADING
12.00-20	B1	20PR	8.5	1125	315	880	3900
12.00-20	B2	20PR	8.5	1125	315	880	3900
12.00-20	B2	18PR	8.5	1125	315	810	3730
12.00-20	T2	18PR	8.5	1125	315	810	3730
12.00-20	T3	18PR	8.5	1125	315	810	3730
11-22.5TL	T2	12PR	8.25	1054	279	580	2465
11.00-20	B2	18PR	8.0	1085	293	910	3550
11.00-20	T2	18PR	8.0	1085	293	910	3550
11.00-20	T2	16PR	8.0	1085	293	810	3270
11.00-20	B2	16PR	8.0	1085	293	810	3270
11.00-20	T3	16PR	8.0	1085	293	810	3270
10.00-20	B1	16PR	7.5	1055	278	810	3000

10.00-20	B2	16PR	7.5	1055	278	810	3000
10.00-20	T2	16PR	7.5	1055	278	810	3000
10.00-20	M1	16PR	7.5	1055	278	810	3000
10.00-20	T3	16PR	7.5	1055	278	810	3000
9.00-20	B2	16PR	7.0	1018	259	880	2800
9.00-20	T3	16PR	7.0	1018	259	880	2800
9.00-20	T2	16PR	7.0	1018	259	880	2800
8.25-20	B1	14PR	6.5	974	235	810	1885
8.25-20	T2	14PR	6.5	974	235	810	1885
7.50-20	B1	14PR	6.0	935	215	810	1885
7.50-20	T2	14PR	6.0	935	215	810	1885
7.50-20	B1	14PR	5.5	904	200	840	1750
7.00-20	B1	10PR	5.5	904	200	630	1430

Light truck tyres

SIZE	PATTERN SERIA NUMBER	PR	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	RELEVANT PRESSURE	MAXLOADING
8.25-16	B3	16PR	6.50H	855	235	730	1850
8.25-16	B3	14PR	6.50H	855	235	630	1705
8.25-16	T2	14PR	6.50H	855	235	630	1705
7.50-17	T2	10PR	6.0	859	215	630	1439
7.50-16	B1	16PR	6.00G	805	215	830	1685
7.50-16	B1	14PR	6.00G	805	215	730	1550
7.50-16	T2	14PR	6.00G	805	215	730	1550
7.50-16	M5	8PR	6.00G	805	215	420	1105
7.50-16	M5	14PR	6.00G	805	215	730	1550
7.50-16	T2	14PR	6.00G	805	215	730	1550
7.50-16	T1	12PR	6.00G	805	215		
7.50-16	T2	10PR	6.00G	805	215	530	1260
7.50-16	M7	10PR	6.00G	805	215	530	1260
7.50-16	M7	8PR	6.00G	805	215	420	1105
7.50-16	T2	12PR	6.00G	780	215	630	1370
7.50-14	T2	8PR	51/2J	691	190	250	640
7.00-16	B1	14PR	5.50F	775	200	730	1320
7.00-16	B4	10PR	5.50F	775	200	530	1040
7.00-16	B1	16PR	5.50F	775	200	830	1420
7.00-16	T2	14PR	5.50F	775	200	730	1320
7.00-16	B1	12PR	5.50F	775	200	630	1220
7.00-16	T2	12PR	5.50F	775	200	630	

Industrial tyres

SIZE	PATTERN SERIA NUMBER	PR	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	RELEVANT PRESSURE	MAXLOADING
12.00-20	PLT328	22PR	8.5	1125	315	965	7820
12.00-20	PLT328	20PR	8.5	1125	315	880	7400
12.00-20	PLT338	18PR	8.5	1125	315	800	7120
12.00-20	PLT338	18PR	8.5	1125	315	800	7120
12.00-20	PLT338	16PR	8.5	1125	315	700	6960
10.00-20	PLT338	16PR	7.5	1055	278	775	6025
9.00-20	PLT338	14PR	7.0	1018	259	750	5155
9.00-16	L6	14PR	6.50H	890	255	760	4495
9.00-16	PLT328	14PR	6.50H	890	255	760	4495
6.00-15.叉车胎	PLT328	10PR	4.50E	705	170	825	2615
5.70-8.叉车胎	TDT100	10PR	3.50D	470	137	900	1295
5.50-15.叉车胎	PLT328	8PR	4.50E	670	157	700	1970
5.00-8.叉车胎	L6	10PR	3.50D	470	137	900	1295
5.00-8.叉车胎	SD2000	10PR	3.50D	470	137	900	1295
5.00-8.叉车胎	PLT328	10PR	3.50D	470	137	900	1295
5.00-8.叉车胎	P222	10PR	3.50D	470	137	900	1295
4.50-12.叉车胎	PLT328	8PR	3.00B	548	122	725	1040
15*12/4-8.叉车胎	B1	12PR	3.25L	385	122	900	950
8.25-15	PLT328	16PR	6.5	840	235	900	4750
8.25-15	P222	16PR	6.5	840	235	900	4750
8.25-15	TDT100	16PR	6.5	840	235	900	4750
8.25-15	SD2000	16PR	6.5	840	235	900	4750
8.25-15	PLT328	14PR	6.5	840	235	800	4435
8.25-15	P222	14PR	6.5	840	235	800	4435
8.25-15	TDT100	14PR	6.5	840	235	800	4435
8.25-15	SD2000	14PR	6.5	840	235	800	4435
8.25-15	L6	14PR	6.5	840	235	800	4435
8.25-15	T800	14PR	6.5	840	235	800	4435
8.25-15	PLT328	12PR	6.5	840	235	700	4100
8.25-15	P222	12PR	6.5	840	235	700	4100
8.25-15	TDT100	12PR	6.5	840	235	700	4100
8.25-15	T800	12PR	6.5	840	235	700	4100
8.25-15	SD2000	12PR	6.5	840	235	700	4100
8.25-15	L6	12PR	6.5	840	235	700	4100
8.25-12	L6	12PR	6.5	765	235	750	3750
7.50-15	L6	14PR	6.00G	780	215	875	3950
7.50-15	PLT328	14PR	5.00G	780	215	875	3950
7.50-15	P222	14PR	6.00G	780	215	875	3950
7.50-15	T800	14PR	6.00G	780	215	875	3950
7.50-15	SD2000	14PR	6.00G	780	215	875	3950
7.50-15	SD2000	12PR	6.00G	780	215	775	3630
7.50-15	PLT328	12PR	6.00G	780	215	775	3630
7.50-15	P222	12PR	6.00G	780	215	775	3630
7.50-15	T800	12PR	6.00G	780	215		

Solid tyres for pneumatic tyres rims

SIZE	PATTERN SERIA NUMBER	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	LOAD	ROTATION
8.25-15	SP800	6.5	847	236	4940	3950
8.25-12	SP800	6.5	735	236	4320	3455
7.50-15	SP800	6.50H	774	215	4360	3490
7.00-15	SP800	5.50S	759	204	3590	2872
7.00-12	SP800	5.00S	683	192	3015	2410
7.00-9	SP800	5.00S	578	186	2730	2200
6.50-10	SP800	5.00F	597	178	2640	2110
6.00-9	SP800	4.00E	545	175	1920	1535
5.00-8	SP800	3.00D	469	146	1210	970
28*9-15	SP800	7.0	706	221	4090	3270
23*9-10	SP800	6.50F	595	225	3420	2735
21*8-9	SP800	6.00E	535	207	2810	2250
18*7-8	SP800	4.33R	457	170	2350	1880

Press-on solid

SIZE	PATTERN SERIA NUMBER	SIZE(MM)	LOAD	ROTATION
22*12*16	C1	559*305*406.4	5235	4660
22*9*16	C1	559*229*406.4	3750	3340
22*8*16	C1	559*203*406.4	3260	2900
22*7*16	C1	559*178*406.4	2760	2440
21*9*15	C1	533*229*381	3620	3220
21*8*15	C1	533*203*381	3140	2795
21*7*15	C1	533*178*381	2670	2380
21*6*15	C1	533*152*308	2190	1940
20*8*16	C1	508*203*406.4	2790	2480
18*9*121/8	C1	457*229*308	3215	2860
18*8*121/8	C1	457*203*308	2790	2480
18*7*121/8	C1	457*178*308	2370	2110
18*6*121/8	C1	457*152*308	1950	1740
18*5*121/8	C1	457*127*308	1530	1360
161/4*6*111/4	C1	413*152*285.8	1780	1580
161/4*5*111/4	C1	413*127*285.8	1415	1260
16*6*101/2	C1	406*152*266.7	1780	1580
16*5*101/2	C1	406*127*266.7	1400	1250
15*5*111/4	C1	381*127*285.8	1290	1150
14*41/2*8	C1	356*114*203.2	1090	970
131/2*51/2*8	C1	343*140*203.2	1400	1250
101/2*5*61/2	C1	267*127*165.1	1000	890
10*5*61/2	C1	254*127*165.1	940	840
10*4*61/2	C1	254*102*165.1	720	640
9*5*5	C1	229*127*127	890	790